

<h1>Declaration of Performance</h1>	
-------------------------------------	--

Nº: 002AR2013

- 1.- Unique identification code of the product type
Dry pressed Glazed tile, internal and/or external flooring and wall finishes
2. Intended use(s)
For internal and/or external flooring and wall finishes
3. Name or registered trade mark, and contact address of the manufacturer

**Arcana Cerámica S.A.
 Ctra.Castellón Km 23,6
 12110 Castellón (CASTELLON-ESPAÑA)**
4. System of assessment and verification of constancy of performance.
System 4
5. Name and identification number of notified laboratory, if relevant.
6. Declared Performances

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	Class A1 – A1 _n	EN 14411:2012
Release of dangerous substance , for:		
- Cadmium	NPD	
- Lead	NPD	
Breaking strength	> 1100 N	
Slipperiness	NPD	
Bond strength/adhesión, for:		
- Cementitious adhesive, type C1	> 0,5 N/mm ²	
Thermal shock resistance	Pass	
Durability for:		
- Internal use	Pass	
- External use: freeze-thaw resistance	Pass	
Tactility	NPD	

Signature :

ARCANA CERAMICA S.A. N.I.F. A-12449047
 CTRA. CASTELLÓN, KM. 23,6
 12110 ALCORÁ (CASTELLÓN-ESPAÑA)

Date : 2013-07-01

Name: Víctor Prieto López
Position: Managing Director